



HoistCam™ Mini HC120 (Deprecated)

Blind lifts for cranes where line-of-sight is impossible for the operator are now a thing of the past. The cost effective three-part wireless HC120 series HoistCam™ from Netarus is designed to place the eyes of the operator anywhere. Safety is increased, and efficiency improved by making visual information available to those who need it.



**Mini Video Transmission
Box (VRB)**

**Mounts Quickly
To Any
Magnet Surface**



9.7in Monitor in Operator's Cab

**The HC120 has been
Replaced by the
HoistCam i-Series
HC140i**

FEATURES

- IP67 rated weatherproof camera
- Fixed lens camera
- Magnetic mount (no drilling)
- Integrated wireless transmitter with up to 2000ft range
- Powered at boom tip with 12VDC to 24VDC
- 2.4Ghz directional wireless antenna and receiver
- Base magnets to mount to any magnetic surface
- 9.7in display with heavy duty RAM® suction cup mount
- Infrared illuminators for night time viewing
- Operating temperatures between -10°C to +50°C

OPTIONAL FEATURES

- Support for multiple types of cranes including tower, luffing, crawler, telescopic, overhead and more
- 12VDC power adapter for VTB and camera
- Battery pack for wireless VTB and camera
- Number of cameras can range from 1 to 4.
- Split screen supports one image, two side-by-side or quad split screen.
- Remote monitor or recording with HoistCam Director
- U-bolt or permanent display mount