



WIRED BALL CAMERA HC100



Blind lifts for cranes where line-of-sight is impossible for the operator are now a thing of the past. The cost effective wired and rugged ball camera for the HC100 Gen 2 series HoistCam™ from Netarus is designed to place the eyes of the operator anywhere. Safety is increased, and efficiency improved by making visual information available to the operator.

FEATURES

- ▶ IP69k rated weatherproof camera
- ▶ Fixed lens camera of 102 degrees
- ▶ Powered at VB with 12VDC or 24VDC
- ▶ Base magnets on camera to mount to any magnetic surface (no drilling)
- ▶ 9.7in display with heavy duty RAM@ suction cup mount
- ▶ Infrared illuminators for night time viewing with 30ft light range
- ▶ Camera operating temperatures between -30°C to +75°C

RECOMMENDED UPGRADES

- ▶ Support for multiple types of cranes including tower, luffing, crawler, telescopic, overhead and more
- ▶ Custom cable length between VRB and mini HoistCam
- ▶ Number of cameras can range from 1 to 4
- ▶ Split screen supports one image, two side-by-side or quad split screen
- ▶ Remote monitor or recording with HoistCam Director
- ▶ U-bolt or permanent display mount

**MOUNTS QUICKLY
TO ANY MAGNETIC
SURFACE**

**ASK ABOUT AVAILABLE CUSTOMIZATION
OPTIONS SPECIFIC TO YOUR CRANE
APPLICATION**